

PHYSIO FLOW™

Noninvasive Cardiac Output

PHYSIO FLOW VS-6

ACCURATE AND EASY



NEW : PhysioFlow CO Parameters

- Stroke Volume
- Cardiac Output / Index, fully validated
- Contractility
- Left Ventricular Ejection Time
- Ejection Fraction (estimate)
- Early Diastolic Filling Ratio
- Systemic Vascular Resistance
- Left Cardiac Work index

And Multiparametric Monitoring

- 3- or 5-lead ECG Cables
- I, II, III, V Lead ECG
- Non Invasive Blood Pressure
- Resp. Rate
- SpO₂
- Temperature

Monitor Features

- 2.5" Thin
- 8.4" High Brightness Color Display
- Light Weight: 5lb (with battery)
- 4.5 Hour Li-Ion Battery (standard)
- Splash-Proof Case
- Defibrillation Proof
- Rich Set-Up for Local Biomed's Analysis and Preventive Maintenance
- Trend Reports and Hemodynamic Cross
- Easy Software Use and Upgrades
- Stored ECG/Vital Signs/Trend Reports
- RS232 Interface to PC
- Easy to Clean
- Rugged Cable Connections

Features of device may change. Governmental approvals pending



www.physioflow.com

physioflow@yahoo.com